

# Audi SQ6 Sportback e-tron



360 kW

## Drivetrain / transmission / battery

|                                                         |                           |
|---------------------------------------------------------|---------------------------|
| Drive type                                              | All-wheel drive           |
| Number of electric motors front axle / rear axle        | 1 / 1                     |
| Max. electrical output with push-to-pass function in kW | 360                       |
| Max. electrical output in launch control mode in kW     | 380                       |
| Electrical torque output front / rear in Nm (lb-ft)     | 275 / 580 (202.8 / 427.8) |
| Battery type / number of cells                          | Lithium-ion / 180         |
| Gross / net battery capacity in kWh                     | 100 / 94.9                |
| Max. charging capacity AC / DC in kW                    | 11 / 270                  |
| Charging time DC 10–80% in min                          | 21                        |
| Charging time AC 0–100%, 3ph 16A@230V in min            | 600                       |
| On-board voltage 1 in volts                             | 12                        |
| Voltage level of the HV battery in volts                | 800                       |

## Suspension / steering / brakes

|                                             |                                                                                                                                                 |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Type and design of front-axle suspension    | 5-link front axle                                                                                                                               |
| Type and design of rear-axle suspension     | 5-link rear axle                                                                                                                                |
| Tires (basic)                               | 255 / 50 R 20   285 / 45 R 20                                                                                                                   |
| Wheels (basic)                              | Cast aluminum flow forming 8.5 J x 20   Cast aluminum flow forming 10 J x 20                                                                    |
| Steering                                    | Electromechanical progressive steering with speed-dependent power assistance                                                                    |
| Steering ratio                              | 16.3                                                                                                                                            |
| Turning circle in m (ft)                    | 12.1 (39.7)                                                                                                                                     |
| Brake system                                | ESC/ABS/EBD/ brake unit, hydraulic brake assist; front: aluminum fixed caliper; rear: floating caliper with integrated electronic parking brake |
| Brake disk diameter front / rear in mm (in) | 375 (14.8) / 350 (13.8)                                                                                                                         |

## Performance / range

|                                                                            |                           |
|----------------------------------------------------------------------------|---------------------------|
| Top speed in km/h (mph)                                                    | 230 (142.9)               |
| electrical acceleration, 0–100 km/h (62.1 mph) in s                        | 4.4                       |
| Electrical acceleration in launch control mode, 0–100 km/h (62.1 mph) in s | 4.3                       |
| Electrical range, combined in km (mi)                                      | 578 – 604 (359.2 – 375.3) |

## Consumption / emission<sup>1</sup>

|                                                              |             |
|--------------------------------------------------------------|-------------|
| Electric power consumption, combined in kWh/100 km (62.1 mi) | 18.1 – 17.3 |
| CO <sub>2</sub> emissions, combined in g/km (g/mi)           | 0           |
| CO <sub>2</sub> class                                        | A           |

---

### **Servicing / guarantee (Germany)**

|                                                                                                |                  |
|------------------------------------------------------------------------------------------------|------------------|
| Service interval                                                                               | 2 years          |
| Vehicle / paint / rust perforation guarantee                                                   | 2 / 3 / 12 years |
| Insurance classification in Germany:<br>third party / fully comprehensive / part-comprehensive | 20 / 29 / 26     |

---

### **Weights / loads**

|                                                                             |                                                |
|-----------------------------------------------------------------------------|------------------------------------------------|
| Unladen weight without driver / with driver / gross weight limit in kg (lb) | 2350 / 2425 / 2965 (5180.9 / 5346.2 / 6536.7)  |
| Front / rear axle load limit in kg (lb)                                     | 1395 / 1655 (3075.4 / 3648.7)                  |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)      | 2400 / 2400 // 750 (5291.1 / 5291.1 // 1653.5) |
| Roof load limit / permissible nose weight in kg (lb)                        | 75 / 100 (165.3 / 220.5)                       |

---

### **Dimensions<sup>2</sup> / body**

|                                                                            |                                                       |
|----------------------------------------------------------------------------|-------------------------------------------------------|
| Body type / number of doors / number of seats                              | Unitary steel/aluminum composite construction / 5 / 5 |
| Drag coefficient C <sub>d</sub> / frontal area A in m <sup>2</sup> (sq ft) | 0.30 / 2.68 (28.8)                                    |
| Vehicle height from – to in mm (ft)                                        | 1611 – 1665 (5.3 – 5.5)                               |
| Vehicle length from – to in mm (ft)                                        | 4771 – 4771 (15.7 – 15.7)                             |
| Vehicle width, without mirrors, from – to in mm (ft)                       | 1939 – 1965 (6.4 – 6.4)                               |
| Vehicle width, including mirrors, in mm (ft)                               | 2193 (7.2)                                            |
| Wheelbase (full load) from – to // track width front/rear in mm (ft)       | 2893 – 2899 (9.5 – 9.5) // 1676 / 1659 (5.5 / 5.4)    |
| Overhang angle, front / rear in degrees                                    | 16.3 / 23.7                                           |
| Height of loading edge from – to in mm (ft)                                | 746 – 777 (2.4 – 2.5)                                 |
| Luggage compartment front (frunk) in l (cu ft)                             | 64 (2.3)                                              |
| Luggage compartment behind the 2 <sup>nd</sup> seat row in l (cu ft)       | 499 (17.6)                                            |
| Largest luggage capacity behind the 1 <sup>st</sup> seat row in l (cu ft)  | 1361 (48.1)                                           |

Program for Germany, Status: 02/02/26

<sup>1</sup> Information on power consumption and CO<sub>2</sub> emissions in range depending on the chosen equipment level of the car.  
<sup>2</sup> Value ranking taking into account different chassis and equipment lines in relation to the basis model.