

Audi A6 allroad

e-hybrid quattro 270 kW S tronic



Engine / electrics

Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 10.5
Max. power output in kW (PS) / at rpm	185 (252) / 5000 – 6500
Max. torque in Nm (lb-ft) / at rpm	380 (280.3) / 1600 – 4500
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6e-bis
Charging time AC 0–100%, 3ph 16A@230V in min	150
Max. charging capacity AC in kW	11
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	400

Hybrid

Battery type (high-voltage) / number of cells	Lithium-Ion / 102
Gross / net battery capacity in kWh	25.9 / 22.0
Max. system output in kW (PS)	270 (367)
Peak electrical output in kW	105
Continuous electrical output in kW	55
Total system torque output in Nm (lb-ft)	500 (368.8)
Electrical torque output in Nm (lb-ft)	350 (258.1)

Drivetrain / transmission

Drive type	quattro all-wheel drive with ultra technology
Type of center differential	Electronically controlled multi-plate clutch
Type of rear axle differential	quattro ultra
Clutch	Hydraulically actuated dual clutch (wet)Electronically controlled multi-plate clutch
Transmission type	7-speed S tronic
Transmission ratio in 1 st /2 nd gear	3.188 / 2.190
Transmission ratio in 3 rd /4 th gear	1.517 / 1.057
Transmission ratio in 5 th /6 th gear	0.738 / 0.557
Transmission ratio in 7 th /8 th gear	0.433 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.750 / 4.410 / -

Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Wheels (basic) // Tires (basic)	Cast aluminum flow forming 9 J x 19 // 265 / 45 R 19
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	13.1
Turning circle in m (ft)	11.4 (37.4)
Brake system	ESC/ABS/EBD, brake unit, hydraulic brake assist; Front: floating calipers; Rear: floating calipers with integrated electronic parking brake
Brake disk diameter front / rear in mm (in)	360 / 350 (14.2 / 13.8)

Performance / range

Top speed / electrical in km/h (mph)	250 (155.3) / 140 (87.0)
System acceleration, 0–100 km/h (0–62.1 mph)	5.5
Electrical range, City (EAER) in km (mi)	up to 114 (70.8)
Electrical range, combined (EAER) in km (mi)	92 – 102 (57.2 – 63.4)
Fuel type / octane value / fuel standard	Electricity / Gasoline / 95 / DIN EN 228

Consumption / emission¹

Fuel consumption, weighted combined, in l/100 km (US mpg)	2.8 – 2.3 (84.0 – 102.3)
Electric power consumption, weighted combined, in kWh/100 km (62.1 mi)	17.0 – 16.2
CO ₂ emissions, weighted combined, in g/km (g/mi)	64 – 53 (103.0 – 85.3)
CO ₂ class, weighted combined	B
Fuel consumption with discharged battery, combined, in l/100 km (US mpg)	7.7 – 7.0 (30.5 – 33.6)
CO ₂ emissions with discharged battery, combined, in g/km (g/mi)	174 – 159 (280.0 – 255.9)
CO ₂ class with discharged battery	F

Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 Jahre
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	19 / 27 / 28

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (lb)	2205 / 2280 / 2800 (4861.2 / 5026.5 / 6172.9)
Front / rear axle load limit in kg (lb)	1280 / 1605 (2821.9 / 3538.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	2000 / 2000 // 750 (4409.2 / 4409.2 // 1653.5)
Roof load limit / permissible nose weight in kg (lb)	100 / 100 (220.5 / 220.5)

Capacities

Cooling system capacity (incl. heating) in l (US gal)	20.1 (5.3)
Engine oil capacity, including filter (change volume) in l (US qt)	6 (6.3)
Fuel tank capacity / optional in l (US gal)	46 (12.2) / -

Dimensions² / body

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5 / 5
Drag coefficient C_d / frontal area A in m ² (sq ft)	0.31 / 2.45 (26.4)
Vehicle height from – to in mm (ft)	1479 – 1508 (4.9 – 4.9)
Vehicle length from – to in mm (ft)	5016 – 5016 (16.5 – 16.5)
Vehicle width, without mirrors, from – to in mm (ft)	1986 – 1986 (6.5 – 6.5)
Vehicle width, including mirrors, in mm (ft)	2099 (6.9)
Wheelbase (full load) from – to // track width front/rear in mm (ft)	2931 – 2932 // 1700 / 1680 (9.6 – 9.6 // 5.6 / 5.5)
Overhang angle, front / rear in degrees	15.1 / 17.6
Height of loading edge from – to in mm (ft)	680 – 693 (2.2 – 2.3)
Luggage compartment behind the 2 nd seat row in l (cu ft)	404 (14.3)
Largest luggage capacity behind the 1 st seat row in l (cu ft)	1423 (50.3)

Program for Germany, Status: 07/09/2026

¹ Information on fuel/power consumption and CO₂ emissions in ranges depending on the chosen equipment level of the car.

² Value range taking into account different chassis and equipment lines in relation to the basic model.