

# Audi A2 e-tron



125 kW

## Drivetrain / transmission / battery

|                                                  |                   |
|--------------------------------------------------|-------------------|
| Drive type                                       | Rear-wheel drive  |
| Number of electric motors front axle / rear axle | - / 1             |
| Max. electrical output in kW                     | 125               |
| Total electrical torque output in Nm (lb-ft)     | 350 (258.1)       |
| Battery type / number of cells                   | Lithium-Ion / 208 |
| Gross / net battery capacity in kWh              | 52 / 50           |
| Max. charging capacity AC / DC in kW             | 11 / 100          |
| Charging time DC 10–80% in min                   | 24                |
| Charging time AC 0–100%, 3ph 16A@230V in min     | 330               |
| On-board voltage 1 in volts                      | 12                |
| Voltage level of the HV battery in volts         | 400               |

## Suspension / steering / brakes

|                                          |                                                                                                                            |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Type and design of front-axle suspension | McPherson struts, front                                                                                                    |
| Type and design of rear-axle suspension  | 4-link rear axle                                                                                                           |
| Tires (basic)                            | 225 / 50 R 18                                                                                                              |
| Wheels (basic)                           | Cast aluminum 7.5 J x 18                                                                                                   |
| Steering                                 | Electromechanical assisted steering                                                                                        |
| Steering ratio                           | 16                                                                                                                         |
| Turning circle in m (ft)                 | 10.9 (35.8)                                                                                                                |
| Brake system                             | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper |

## Performance / range

|                                                     |                           |
|-----------------------------------------------------|---------------------------|
| Top speed in km/h (mph)                             | 160 (99.4)                |
| electrical acceleration, 0–100 km/h (62.1 mph) in s | 8.8                       |
| Electrical range, combined in km (mi)               | 376 – 423 (233.6 – 262.8) |

## Consumption / emission<sup>1</sup>

|                                                              |             |
|--------------------------------------------------------------|-------------|
| Electric power consumption, combined in kWh/100 km (62.1 mi) | 15.7 – 13.7 |
| CO <sub>2</sub> emissions, combined in g/km (g/mi)           | 0           |
| CO <sub>2</sub> class                                        | A           |

---

### **Servicing / guarantee (Germany)**

|                                                                                                |                  |
|------------------------------------------------------------------------------------------------|------------------|
| Service interval                                                                               | 2 years          |
| Vehicle / paint / rust perforation guarantee                                                   | 2 / 3 / 12 years |
| Insurance classification in Germany:<br>third party / fully comprehensive / part-comprehensive | 14 / 19 / 20     |

---

### **Weights / loads**

|                                                                             |                                               |
|-----------------------------------------------------------------------------|-----------------------------------------------|
| Unladen weight without driver / with driver / gross weight limit in kg (lb) | 1840 / 1915 / 2400 (4056.5 / 4221.9 / 5291.1) |
| Front / rear axle load limit in kg (lb)                                     | 1105 / 1340 (2317.1 / 2954.2)                 |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)      | 1600 / 1600 // 750 (3527.4 / 3527.4 / 1653.5) |
| Roof load limit / permissible nose weight in kg (lb)                        | 75 / 75 (165.3 / 165.3)                       |

---

### **Dimensions<sup>2</sup> / body**

|                                                                           |                                                     |
|---------------------------------------------------------------------------|-----------------------------------------------------|
| Body type / number of doors / number of seats                             | Unitary steel / 5 / 5                               |
| Drag coefficient $C_d$ / frontal area A in m <sup>2</sup> (sq ft)         | 0.24 / 2.38 (25.6)                                  |
| Vehicle height from – to in mm (ft)                                       | 1548 – 1583 (5.1 – 5.2)                             |
| Vehicle length from – to in mm (ft)                                       | 4324 – 4324 (14.2 – 14.2)                           |
| Vehicle width, without mirrors, from – to in mm (ft)                      | 1789 – 1789 (5.9 – 5.9)                             |
| Vehicle width, including mirrors, in mm (ft)                              | 2039 (6.7)                                          |
| Wheelbase (full load) from – to // track width front/rear in mm (ft)      | 2768 – 2770 // 1542 / 1520 (9.1 – 9.1 // 5.1 / 5.0) |
| Height of loading edge from – to in mm (ft)                               | 764 – 777 (2.5 – 2.5)                               |
| Luggage compartment behind the 2 <sup>nd</sup> seat row in l (cu ft)      | 396 (14.0)                                          |
| Largest luggage capacity behind the 1 <sup>st</sup> seat row in l (cu ft) | 1336 (47.2)                                         |

Program for Germany, Status: 10/01/26

<sup>1</sup> Information on power consumption and CO<sub>2</sub> emissions in range depending on the chosen equipment level of the car.

<sup>2</sup> Value ranking taking into account different chassis and equipment lines in relation to the basis model.